

ZIISOR Product Catalogue-400M/470M/490MHz



Note:

- Below are ZIISOR standard products for 400M/470M/490MHz.
- ZIISOR offers customization as well if the standard products cannot fulfill your needs.

For any question, please contact us at:

Tel.: +86-028-61542639 Email: support@ziisor.com
Wechat: coco468479 Whatsapp: +86 19180530714

No.	Center frequency	P/N	Model No.	Category	Typical Characteristics	Frequency Band	Connector	Gain	Height/ Size/ Dimension	Photo
1	400MHz	10058	TX400-BLG-55 (classic)	Fiberglass	Waterproof, antifreeze, strong sealing, and high gain	410-510MHz	N-J	6dBi	55cm	
2	490MHz	10082	TX490-BLG-120 (classic)	Fiberglass	Waterproof, antifreeze, strong sealing, and high gain	470-510MHz	N-J	8dBi	120cm	
3	490MHz	10112	TX490-BLG-12	Fiberglass	Waterproof, antifreeze, strong sealing, and high gain	470-510MHz	N-J	2.5dBi	12cm	
4	470MHz	10118	TX470-BLG-12	Fiberglass	Waterproof, antifreeze, strong sealing, and high gain	460-480MHz	N-J	2.5dBi	12cm	
5	470MHz	10111	TX470-BLG-55	Fiberglass	Waterproof, antifreeze, strong sealing, and high gain	450-510MHz	N-J	6dBi	55cm	
6	490MHz	10119	TX490-BLG-15	Fiberglass	Waterproof, antifreeze, strong sealing, and high gain	445-515MHz	N-J	3dBi	15cm	
7	470MHz	10120	TX470-BLG-40	Fiberglass	Waterproof, antifreeze, strong sealing, and high gain	455-490MHz	N-J	4.5dBi	40cm	
8	490MHz	10121	TX490-BLG-40	Fiberglass	Waterproof, antifreeze, strong sealing, and high gain	475-515MHz	N-J	4.5dBi	40cm	
9	490MHz	30199	TX490-JZ-5	Rubber	Small size, high cost-effectiveness, and elbows	470-510MHz	SMA-J	2dBi	50mm	
10	490MHz	30200	TX490-JW-5	Rubber	Small size, high cost-effectiveness, and elbows	470-510MHz	SMA-J	2dBi	48mm	
11	490MHz	30310	TX490-JK-11	Rubber	High cost-effectiveness, bendable	470-510MHz	SMA-J	2.5dBi	110mm	
12	490MHz	20118	TX490-JKD-20 (classic)	Rubber	High cost-effectiveness, pure copper oscillator with inner core, high efficiency	470-510MHz	SMA-J	3.5dBi	200mm	
13	490MHz	20075	TX490-JKD-20P	Rubber	Balanced feeding, higher efficiency, bendable, knife shaped	470-510MHz	SMA-J	4dBi	200mm	
14	470MHz	20061	TX470-JKD-20	Rubber	High cost-effectiveness, pure copper oscillator with inner core, high efficiency	460-480MHz	SMA-J	3.5dBi	200mm	
15	470MHz	30049	TX470-JZR-9 (classic)	Rubber	Small size, high cost-effectiveness, soft rubber stick	460-480MHz	SMA-J	3dBi	90mm	
16	470MHz	30035	TX470-JZLW-15	Rubber	Integrated waterproofing	460-480MHz	IPXE	3dBi	height165mm , Feeder length150mm	
17	470MHz	30142	TX470-JKS-IPX20	Cabinet	Integrated waterproofing	461-476MHz	IPX 1代	3dBi	height 165mm , Feeder length 150mm	
18	490MHz	30036	TX490-JZLW-15 (classic)	Cabinet	Integrated waterproofing	470-510MHz	IPXE	3dBi	height165mm , Feeder length150mm	

19	490MHz	30348+	TX490-XPL10	Magnetic	High cost-effectiveness and flexible installation	470-510MHz	SMA-J	2.5dBi	124*30mm Optional suction cup base size and extension cable length	
20	490MHz	30349+	TX490-XPL12	Magnetic	High cost-effectiveness and flexible installation	470-510MHz	SMA-J	3dBi	148*30mm Optional suction cup base size and extension cable length	
21	490MHz	20124+	TX490-XPL28	Magnetic	High cost-effectiveness and flexible installation	470-510MHz	SMA-J	4dBi	308*30mm Optional suction cup base size and extension cable length	
22	490MHz	30390	TX490-TH-3	Spring Antenna	Low cost, built-in spring	/	weld	1dBi	37mm	
23	490MHz	30293	TX490-TH-29Z	Spring Antenna	Low cost, built-in spring	/	weld	1dBi	29mm	
24	470MHz	20132	TH470-TH-28W	Spring Antenna	Low cost, built-in spring	/	weld	1dBi	28mm	