

ZIISOR Product Catalogue - WiFi Dual Band



Note:



1. Below are ZIISOR standard products for 2.4GHz/ 5.8GHz WiFi dual band.
2. ZIISOR offers customization as well if the standard products cannot fulfill your needs.

For any question, please contact us at:

Tel.: +86-028-61542639 Email.: support@ziisor.com
Wechat: coco468479 Whatsapp: +86 19180530714

No.	P/N	Model No.	Category	Typical Characteristics	Frequency Band	Connector	Gain	Height/ Size/ Dimension	Photo
1	10085	TXWF-BLG-18	Fiberglass	waterproof, freezeproof and well sealed	2.4-2.5GHz; 5.15-5.85GHz	N-male	4/4dBi	18cm	
2	10055	TXWF-BLG-26	Fiberglass	waterproof, freezeproof and well sealed, high gain	2.4-2.5GHz; 5.15-5.85GHz	N-male	8dBi	26cm	
3	10086	TXWF-BLG-40	Fiberglass	waterproof, freezeproof and well sealed, high gain	2.4-2.5GHz; 5.15-5.85GHz	N-male	6/9dBi	40cm	
4	20085	TXWF-JKS-20 (classic)	Rubber	foldable, cost-effective, high gain	2.4-2.5GHz; 5.15-5.85GHz	SMA-male	5dBi	195mm	
5	20026	TXWF-JKS-20RP	Rubber	foldable, cost-effective, high gain	2.4-2.5GHz; 5.15-5.85GHz	RP-SMA-male	5dBi	195mm	

No.	P/N	Model No.	Category	Typical Characteristics	Frequency Band	Connector	Gain	Height/ Size/ Dimension	Photo
6	30028	TXWF-JKS-20W	Rubber	foldable, cost-effective, high gain, white	2.4-2.5GHz; 5.15-5.85GHz	SMA-male	5dBi	195mm	
7	30051	TXWF-JK-11RP	Rubber	foldable, cost-effective	2.4-2.5GHz; 5.15-5.85GHz	RP-SMA-male	3dBi	110mm	
8	20046	TXWF-JKK-20	Rubber	foldable, cost-effective, high gain	2.4-2.5GHz; 5.15-5.85GHz	SMA-male	6dBi	195mm	
9	20047	TXWF-JKK-20RP	Rubber	foldable, cost-effective, high gain	2.4-2.5GHz; 5.15-5.85GHz	RP-SMA-male	6dBi	195mm	
10	30027	TXWF-JKY-16	Rubber	foldable, cost-effective	2.4-2.5GHz; 5.15-5.85GHz	SMA-male	4dBi	160mm	
11	30029	TXWF-JKY-16RP	Rubber	foldable, cost-effective	2.4-2.5GHz; 5.15-5.85GHz	RP-SMA-male	4dBi	160mm	
12	30356+	TXWF-XPL3	Magnetic	cost-effective, easy installation	2.4-2.5GHz; 5.15-5.85GHz	SMA-male	3dBi	58*30mm magnetic base and cable are selectable	

No.	P/N	Model No.	Category	Typical Characteristics	Frequency Band	Connector	Gain	Height/ Size/ Dimension	Photo
13	30355+	TXWF-XPL19	Magnetic	cost-effective, easy installation, high gain	2.4-2.5GHz; 5.15-5.85GHz	SMA-male	6/8dBi	220*30mm magnetic base and cable are selectable	
14	30156	TXWF-FPC-3710	FPC	built-in flexible FPC, low cost	2.4-2.5GHz; 5.15-5.85GHz	IPEX-1	2.5dBi	37*10mm, cable 120mm	
15	30300	TXWF-PCB-4814	PCB	built-in PCB, low cost	2.4-2.5GHz; 5.15-5.85GHz	IPEX-1	2.5dBi	48*14mm, cable 119mm	
16	30155	TXWF-PCB-3214 (classic)	PCB	built-in PCB, low cost	2.4-2.5GHz; 5.15-5.85GHz	IPEX-1	2.5dBi	32*14mm, cable 120mm	
17	30158	TXWF-PCB-5109 (classic)	PCB	built-in PCB, low cost	2.4-2.5GHz; 5.15-5.85GHz	IPEX-1	2.5dBi	51*9mm, cable 120mm	
18	30159	TXWF-PCB-4212	PCB	built-in PCB, low cost	2.4-2.5GHz; 5.15-5.85GHz	IPEX-1	2.5dBi	42*12mm, cable 120mm	
19	30197	TXWF-PCB-3810	PCB	built-in PCB, low cost	2.4-2.5GHz; 5.15-5.85GHz	IPEX-1	2.5dBi	38*10mm, cable 119mm	

No.	P/N	Model No.	Category	Typical Characteristics	Frequency Band	Connector	Gain	Height/ Size/ Dimension	Photo
20	30198	TXWF-PCB-4008 (classic)	PCB	built-in PCB, low cost	2.4-2.5GHz; 5.15-5.85GHz	IPEX-1	2.5dBi	40*8mm, cable 142mm	