

ZIISOR Product Catalogue-915MHz





Note:

1. Below are ZIISOR standard products for 915MHz.
2. ZIISOR offers customization as well if the standard products cannot fulfill your needs.

For any question, please contact us at:

No.	P/N	Model No.	Category	Typical Characteristics	Frequency Band	Connector	Gain	Height/ Size/ Dimension	Photo
1	10049	TX915-BLG-26 (classic)	Fiberglass	waterproof, freezeproof and well sealed, high gain	740-990MHz	N-J	3dBi	26cm	
2	10052	TX900-BLG-55 (classic)	Fiberglass	waterproof, freezeproof and well sealed, high gain	860-940MHz	N-J	8dBi	55cm	
3	10074	TX900-BLG-55NK	Fiberglass	waterproof, freezeproof and well sealed, high gain	860-940MHz	N-K	8dBi	55cm	
4	10098	TX900-BLG-100 (classic)	Fiberglass	waterproof, freezeproof and well sealed, high gain	850-950MHz	N-J	9.5dBi	100cm	
5	10113	TX915-BLG-40	Fiberglass	waterproof, freezeproof and well sealed, high gain	880-955MHz	N-J	5.5dBi	40cm	
6	10100	TX900-BLG-90P	Fiberglass	Waterproof, antifreeze, strong sealing, high gainWide bandwidth, high-power 150W	670-1000MHz	N-K	13dBi	90cm	
7	10031	TX915-PB-1919 (classic)	Panel	Waterproof, directional, high gain, long communication distance	902-928MHz	N-K	8.5dBi	190*190*27mm	
8	10068	TX915-PB-2626(NK)	Panel	Waterproof, directional, high gain, long communication distance	900-930MHz	N-K	10dBi	260*260*35mm	
9	10067	TX915-PB-5523	Panel	Waterproof, directional, high gain, communication distance waterproof, directional, small angle, high gain, long communication distance, suitable	905-925MHz	N-K	12dBi	550*230*40mm	
10	10041	TX900-PB-1313	Panel	Directional, high gain, long communication distance	850-960MHz	SMA-J	6dBi	134*134*21mm, Line length 1m	
11	10040	TX900-PB-1313(NK) (classic)	Panel	Directional, high gain, long communication distance	850-960MHz	N-K	8dBi	132*132*18mm	
12	10042	TX900-PB-2323 (classic)	Panel	Directional, high gain, long communication distance	850-960MHz	SMA-J	10dBi	231*231*21mm, Line length 1m	
13	10043	TX900-PB-2626(NK)	Panel	Waterproof, directional, high gain, and long communication distance	850-960MHz	N-K	12dBi	258*258*30mm, Line length 0.4m	
14	10039	TX900-PB-4545 (classic)	Panel	Waterproof, directional, high gain, and long communication distance	830-980MHz	N-K	14dBi	445*445*38mm	
15	30335	TX915-JZ-5	Rubber	Small size, high cost-effectiveness, straight head	895-935MHz	SMA-J	2dBi	52mm	
16	30405	TX915-JK-11	Rubber	High cost-effectiveness, bendable	895-935MHz	SMA-J	2.5dBi	110mm	
17	20112	TX915-JKS-20 (classic)	Rubber	High cost-effectiveness, foldable, rat tailed	895-935MHz	SMA-J	3dBi	195mm	

18	20029	TX915-JKS-20RP	Rubber	High cost-effectiveness, foldable, rat tailed, and porous	895-935MHz	RP-SMA-J	3dBi	195mm	
19	20055	TX915-JKD-20 (classic)	Rubber	High cost-effectiveness, bendable, and knife shaped	895-935MHz	SMA-J	3.5dBi	200mm	
20	20017	TX915-JKD-20RP	Rubber	High cost-effectiveness, bendable, blade shape, and inner hole	895-935MHz	RP-SMA-J	3.5dBi	200mm	
21	30143	TX915-JKS-IPX20	Cabinet	Integrated waterproofing	885-935MHz	IPX 1代	3dBi	Height 200mm, Line length 200mm	
22	20130+	TX900-XPL7	Magnetic	High cost-effectiveness and flexible installation	860-960MHz	SMA-J	3dBi	99*30mm Optional suction cup base size and extension cable length	
23	30351+	TX900-XPL15	Magnetic	High cost-effectiveness and flexible installation	860-960MHz	SMA-J	3.5dBi	179*30mm Optional suction cup base size and extension cable length	
24	30350	TX900-XPL23	Magnetic	High cost-effectiveness and flexible installation	860-960MHz	SMA-J	4dBi	260*30mm Optional suction cup base size and extension cable length	
25	20117+	TX900-XPL33	Magnetic	High cost-effectiveness, high gain, and flexible installation	860-960MHz	SMA-J	6dBi	360*30mm Optional suction cup base size and extension cable length	
26	30354+	TX900-XPL23A	Magnetic	High cost-effectiveness, high gain, and flexible installation	860-960MHz	SMA-J	6dBi	261*30mm Optional suction cup base size and extension cable length	
27	30038	TX915-JZLW-15	Cabinet	Integrated waterproofing	860-940MHz	IPXE	3dBi	height165mm, Feeder length150mm	
28	30311	TX915-FPC-4510 (classic)	FPC	Low cost, built-in FPC, soft antenna	900-931MHz	IPXE	3dBi	45*10mm, Feeder length90mm	
29	30192	TX915-FPC-7020	FPC	Low cost, built-in FPC, soft antenna	900-940MHz	IPXE	3.5dBi	70*20mm, Feeder length121mm	
30	30369	TX915-FPC-8521	FPC	Low cost, built-in FPC, soft antenna	900-931MHz	IPXE	4dBi	85*21mm, Feeder length140mm	
31	30032	TX915-PCB-7505	PCB	Low cost, built-in PCB	860-940MHz	IPXE	3dBi	75*5mm, Feeder length 115mm	
32	30328	TX915-PCB-D42	PCB	PCB	910-920MHz	IPXE	3dBi	diameter42mm, Feeder length 118mm	
33	30302	TX915-PCB-9514	PCB	PCB	860-940MHz	IPXE	3dBi	95*14mm, Feeder length 120mm	
34	30314	TX915-FPC-3009	FPC	Low cost, built-in FPC, soft antenna	910-920MHz	IPX 1代	2.5dBi	30*9mm, Feeder length 100mm	
35	10044	TX900-BM-9	Yagi	Directional, high gain, long communication distance	824-960MHz	N-K	12dBi	76*12cm, Line length 0.3m	
36	10045	TX900-BM-14	Yagi	Directional, high gain, long communication distance	824-960MHz	N-K	14dBi	115*12cm, Line length 0.3m	
37	30053	TX915-TH-18	Spring Antenna	Low cost, built-in spring	/	weld	1dBi	17.6mm	