

ZIISOR Product Catalogue -868MHz



Note:

- Below are ZIISOR standard products for 868MHz.
- ZIISOR offers customization as well if the standard products cannot fulfill your needs.

For any question, please contact us at:

Tel.: +86-028-61542639 Email: support@ziisor.com
Wechat: coco468479 Whatsapp: +86 19180530714

No.	P/N	Model No.	Category	Typical Characteristics	Frequency Band	Connector	Gain	Height/ Size/ Dimension	Photo
1	10048	TX868-BLG-26 (classic)	Fiberglass	waterproof, freezeproof and well sealed, high gain	848-888MHz	N male	3dBi	26cm	
2	10036	TX868-BLG-55NK	Fiberglass	waterproof, freezeproof and well sealed, high gain	840-930MHz	N-K	5dBi	55cm	
3	10099	TX868-BLG-55 (classic)	Fiberglass	waterproof, freezeproof and well sealed, high gain	860-940MHz	N male	8dBi	55cm	
4	10052	TX900-BLG-55 (classic)	Fiberglass	waterproof, freezeproof and well sealed, high gain	860-940MHz	N male	8dBi	55cm	
5	10074	TX900-BLG-55NK	Fiberglass	waterproof, freezeproof and well sealed, high gain	860-940MHz	N-K	8dBi	55cm	
6	10098	TX900-BLG-100 (classic)	Fiberglass	waterproof, freezeproof and well sealed, high gain	850-950MHz	N male	9.5dBi	100cm	
7	10114	TX868-BLG-40	Fiberglass	waterproof, freezeproof and well sealed, high gain	826-898MHz	N-J	5.5dBi	40cm	
8	10122	TX868-BLG-100	Fiberglass	waterproof, freezeproof and well sealed, high gain	860-880MHz	N-J	9.5dBi	100cm	
9	10100	TX900-BLG-90P	Fiberglass	waterproof, freezeproof and well sealed, high gain	670-1000MHz	N-K	13dBi	90cm	
10	10041	TX900-PB-1313	Panel	Directional, high gain, long communication distance	850-960MHz	N male	6dBi	134*134*21mm , cable 1m	
11	10040	TX900-PB-1313(NK) (classic)	Panel	Directional, high gain, long communication distance	850-960MHz	N-K	8dBi	132*132*18mm	
12	10042	TX900-PB-2323 (classic)	Panel	Directional, high gain, long communication distance	850-960MHz	N male	10dBi	231*231*21mm , cable 1m	
13	10043	TX900-PB-2626(NK)	Panel	Waterproof, directional, high gain, and long communication distance	850-960MHz	N-K	12dBi	258*258*30mm, cable 0.4m	
14	10039	TX900-PB-4545 (classic)	Panel	Waterproof, directional, high gain, and long communication distance	830-980MHz	N-K	14dBi	445*445*38mm	
15	30003	TX868-JZ-5	Rubber	Small size, high cost-effectiveness, straight head	848-888MHz	N male	2dBi	52mm	
16	30057	TX868-JK-11	Rubber	High cost-effectiveness, bendable	848-888MHz	N male	3dBi	110mm	
17	20054	TX868-JKD-20 (classic)	Rubber	foldable, cost-effective, high gain	848-888MHz	N male	3.5dBi	200mm	
18	20098	TX868-JKD-20RP	Rubber	foldable, cost-effective, high gain	848-888MHz	RP SMA male	3.5dBi	200mm	

19	30144	TX868-JKS-IPX20	Rubber	foldable, cost-effective, high gain	848-948MHz	IPXE 1	3dBi	height 200mm , cable 200mm	
20	20130+	TX900-XPL7	Magnetic	cost-effective, easy installation, high gain	860-960MHz	N male	3dBi	99*30mm magnetic base and cable are selectable	
21	30351+	TX900-XPL15	Magnetic	cost-effective, easy installation, high gain	860-960MHz	N male	3.5dBi	179*30mm magnetic base and cable are selectable	
22	30350	TX900-XPL23	Magnetic	cost-effective, easy installation, high gain	860-960MHz	N male	4dBi	260*30mm magnetic base and cable are selectable	
23	20117+	TX900-XPL33	Magnetic	cost-effective, easy installation, high gain	860-960MHz	N male	6dBi	360*30mm magnetic base and cable are selectable	
24	30354+	TX900-XPL23A	Magnetic	cost-effective, easy installation, high gain	860-960MHz	N male	6dBi	261*30mm magnetic base and cable are selectable	
25	30037	TX868-JZLW-15	Cabinet	Integrated waterproof	848-948MHz	IPEX	3dBi	height 165mm , cable 150mm	
26	10044	TX900-BM-9	Yagi	directional, high gain, long distance transmission	824-960MHz	N-K	12dBi	76*12cm , cable 0.3m	
27	10045	TX900-BM-14	Yagi	directional, high gain, long distance transmission	824-960MHz	N-K	14dBi	115*12cm , cable 0.3m	